

CPR Declaration of Performance (DoP)

DoP reference:

F1 UKCA DOP

 Unique identification code of the product type (in combination with point 2): BS EN 1339:2003 Inc. Corr. No.1 Concrete paving flags - Internal and external flooring and/or roof covering

2. Identification of the construction product:

Ecclefechan & Kilblane works. Concrete paving flags – Class 1 (see dimensions within the CE Mark & DoP insertion)

3. Intended use:

BS EN 1339:2003 Inc. Corr. No.1 Internal and external flooring and/or roof covering

4. Company name:

Hoddam Contracting Company Limited Hoddam Road Ecclefechan Lockerbie United Kingdom DG11 3BY

- 5. Authorised representative: Laura Gilfillan (address as above)
- 6. System of assessment: Attestation Level 4
- 7. Standard and UK Approved body: Not applicable. Attestation Level 4
- 8. European Technical Assessment (ETA): Not applicable

continued...

9. Declared performance:

Essential Characteristics	Declared values (Applicable to Internal, External & Roof)	Test method
Shape and dimensions (Type, profile and dimension)	See applicable listing (below): ((*h*w) - mm 450*450*50 600*600*50 900*600*50 Colours (Gy, Bf, Rd, Ch) - See Data Sheets & chamfered availability for info.	Designation as Section 5.2 BS EN 1340:2003 Inc. Corr. No. 1 For client information only (Not an 'Essential Requirement' for CE Marking)
Reaction to fire (Internal)	Euroclass A1 w ithout test & Deemed to satisfy	Commission Decision 96/603/EC & 2000/553/EC (EN 1339:2003)
Emission of asbestos	No content	Designation as section 4.2 BS EN 1339:2003 Inc. Corr. No. 1
Breaking strength	Class 1 S - 3.5 MPa	Designation as section 5.3.3.1 & 2 BS EN 1339:2003 Inc. Corr. No. 1
Slip/skid resistance	Satisfactory	Designation as section 5.3.5.1 BS EN 1339:2003 Inc. Corr. No. 1
Thermal conductivity (Internal)	Not intended to contribute	Designation as section 5.3.8 BS EN 1339:2003 Inc. Corr. No. 1
Durability	Satisfactory (linked to 5.3.3.1 & 2)	Designation as section 5.3.3.4 BS EN 1340:2003 Inc. Corr. No. 1
Dangerous Substances	Regulatory information: Not classified as dangerous. The product contains no substances contained on either the Substances of Very High Concern (SVHC) in Annex XIV of European Regulation (EC) No. 06 (REACH); or the SVHC Candidate List	BS EN 771-3:2011+A 1:2015. An informative database covering European and national provisions on dangerous substances is available via the following link: http://ec.europa.eu/enterprise/construction/cpd-ds/
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site http://www.hoddamcontracting.co.uk (or will be supplied directly). The appropriate DoP is referenced F1UKCA DOP on the UKCA Regulations page and/or on the formal documentation	CPR DoP Electronic Provision No. 305/2011

10. Declaration

The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for any on behalf of the manufacturer by Laura Gilfillan (General Manager), issued at the address given in point 4, 01 Jan 2023.

Signature: *Laura Gilfillan*

Supporting information:

The UKCA Mark below was issued with your delivery ticket, or accompanying documentation in accordance with the CPR regulations. Accompanying documentation may include the quotation, order acknowledgement or invoice (delivered either in hard-copy or electronic format within an email).

2023 BS EN 1339:2003 Inc. Corr. No.1 UKCA Mark ref. F1 Dated 01 Jan 2023 Concrete paving flags - Internal and external flooring and/or roof covering Hoddam Contracting Company Limited Hoddam Road, Ecclefechan, Lockerbie, United Kingdom, DG11 3BY Product description: Concrete paving flags - Class 1 (see applicable variations below) Intended use: Internal and external flooring and/or roof covering Attestation Level 4				
		Test method		
Essential Characteristics	Declared values (Applicable to Internal, External & Roof)	Test method		
Shape and dimensions (Type, profile and dimension)	See applicable listing (below): (I*h*w) - mm 450*450*50 600*600*50 900*600*50 Colours (Gy, Bf, Rd, Ch) - See Data Sheets & chamfered availability for info.	Designation as Section 5.2 BS EN 1340:2003 Inc. Corr. No. 1 For client information only (Not an 'Essential Requirement' for CE Marking)		
Reaction to fire (Internal)	Euroclass A1 w ithout test & Deemed to satisfy	Commission Decision 96/603/EC & 2000/553/EC (EN 1339:2003)		
Emission of asbestos	No content	Designation as section 4.2 BS EN 1339:2003 Inc. Corr. No. 1		
Breaking strength	Class 1 S - 3.5 MPa	Designation as section 5.3.3.1 & 2 BS EN 1339:2003 Inc. Corr. No. 1		
Slip/skid resistance	Satisfactory	Designation as section 5.3.5.1 BS EN 1339:2003 Inc. Corr. No. 1		
Thermal conductivity (Internal)	Not intended to contribute	Designation as section 5.3.8 BS EN 1339:2003 Inc. Corr. No. 1		
Durability	Satisfactory (linked to 5.3.3.1 & 2)	Designation as section 5.3.3.4 BS EN 1340:2003 Inc. Corr. No. 1		
Dangerous Substances	Regulatory information: Not classified as dangerous. The product contains no substances contained on either the Substances of Very High Concern (SVHC) in Annex XIV of European Regulation (EC) No. 06 (REACH); or the SVHC Candidate List	BSEN 771-3:2011+A 1:2015. An informative database covering European and national provisions on dangerous substances is available via the following link: http://ec.europa.eu/enterprise/construction/cpd-ds/		
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site http://www.hoddamcontracting.co.uk (or will be supplied directly). The appropriate DoP is referenced F1UKCA DOP on the UKCA Regulations page and/or on the formal documentation	CPR DoP Electronic Provision No. 305/2011		

Please contact us should you require any further information.