

BS EN 1339:2003 Inc. Corr. No.1

UKCA Mark ref. F1 Dated 01 Jan 2023

Concrete paving flags - Internal and external flooring and/or roof covering

Hoddam Contracting Company Limited

Hoddam Road, Ecclefechan, Lockerbie, United Kingdom, DG11 3BY

Product description: Concrete paving flags - Class 1 (see applicable variations below)

Intended use: Internal and external flooring and/or roof covering

Attestation Level 4

Essential Characteristics	Declared values (Applicable to Internal, External & Roof)	Test method
Shape and dimensions (Type, profile and dimension)	See applicable listing (below): (I*h*w) - mm 450*450*50 600*600*50 900*600*50 . Colours (Gy, Bf, Rd, Ch) - See Data Sheets & chamfered availability for info.	Designation as Section 5.2 BS EN 1340:2003 Inc. Corr. No. 1 For client information only (Not an 'Essential Requirement' for CE Marking)
Reaction to fire (Internal)	Euroclass A1 without test & Deemed to satisfy	Commission Decision 96/603/EC & 2000/553/EC (EN 1339:2003)
Emission of asbestos	No content	Designation as section 4.2 BS EN 1339:2003 Inc. Corr. No. 1
Breaking strength	Class 1 S - 3.5 MPa	Designation as section 5.3.3.1 & 2 BS EN 1339:2003 Inc. Corr. No. 1
Slip/skid resistance	Satisfactory	Designation as section 5.3.5.1 BS EN 1339:2003 Inc. Corr. No. 1
Thermal conductivity (Internal)	Not intended to contribute	Designation as section 5.3.8 BS EN 1339:2003 Inc. Corr. No. 1
Durability	Satisfactory (linked to 5.3.3.1 & 2)	Designation as section 5.3.3.4 BS EN 1340:2003 Inc. Corr. No. 1
Dangerous Substances	Regulatory information: Not classified as dangerous. The product contains no substances contained on either the Substances of Very High Concern (SVHC) in Annex XIV of European Regulation (EC) No. 06 (REACH); or the SVHC Candidate List	BS EN 771-3:2011+A1:2015. An informative database covering European and national provisions on dangerous substances is available via the following link: http://ec.europa.eu/enterprise/construction/cpd-ds/
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site http://www.hoddamcontracting.co.uk (or will be supplied directly). The appropriate DoP is referenced F1 UKCA DOP on the UKCA Regulations page and/or on the formal documentation	CPR DoP Electronic Provision No. 305/2011