

## CPR Declaration of Performance (DoP)

### DoP reference:

K4 UKCA DOP

### 1. Unique identification code of the product type (in combination with point 2):

BS EN 1340:2003 Inc. Corr. No.1 Concrete kerb units - Internal and External Flooring and/or roof covering

### 2. Identification of the construction product:

Ecclefechan & Kilblane works. Concrete kerb units – Class 1 (see dimensions below & within the CE Mark & DoP insertion)

HB2R6EX	Radius (external)/6m Half Batter HB2	780*255*125
HB2R8EX	Radius (external)/8m Half Batter HB2	780*255*125
HB2R10EX	Radius (external)/10m Half Batter HB2	780*255*125

### 3. Intended use:

BS EN 1340:2003 Inc. Corr. No.1

Internal public transport premises, external uses and road finishes for pedestrian and vehicular areas, and roof coverings

### 4. Company name:

Hoddam Contracting Company Limited  
Hoddam Road  
Ecclefechan  
Lockerbie  
United Kingdom  
DG11 3BY

### 5. Authorised representative:

Laura Gilfillan (address as above)

### 6. System of assessment:

Attestation Level 4

### 7. Standard and UK Approved body:

Not applicable. Attestation Level 4

### 8. European Technical Assessment (ETA):

Not applicable

continued...

## 9. Declared performance:

Essential Characteristics	Declared values (Applicable to Internal, External & Roof)	Test method												
Shape and dimensions (Type, profile and dimension)	<table border="0"> <tr> <td><b>Class 1 Kerb Units</b></td> <td><b>Radius (external)/</b></td> <td><b>Dimensions (l*h*w) - mm</b></td> </tr> <tr> <td>HB2R6EX</td> <td>6m Half Batter HB2</td> <td>780*255*125</td> </tr> <tr> <td>HB2R8EX</td> <td>8m Half Batter HB2</td> <td>780*255*125</td> </tr> <tr> <td>HB2R10EX</td> <td>10m Half Batter HB2</td> <td>780*255*125</td> </tr> </table>	<b>Class 1 Kerb Units</b>	<b>Radius (external)/</b>	<b>Dimensions (l*h*w) - mm</b>	HB2R6EX	6m Half Batter HB2	780*255*125	HB2R8EX	8m Half Batter HB2	780*255*125	HB2R10EX	10m Half Batter HB2	780*255*125	Designation as Section 5.2 BS EN 1340:2003 Inc. Corr. No. 1 For client information only (Not an 'Essential Requirement' for CE Marking)
<b>Class 1 Kerb Units</b>	<b>Radius (external)/</b>	<b>Dimensions (l*h*w) - mm</b>												
HB2R6EX	6m Half Batter HB2	780*255*125												
HB2R8EX	8m Half Batter HB2	780*255*125												
HB2R10EX	10m Half Batter HB2	780*255*125												
Reaction to fire (Internal)	Euroclass A1 w without test & Deemed to satisfy	Commission Decision 96/603/EC & 2000/553/EC (EN 1340:2003)												
Emission of asbestos	No content	Designation as section 4.2 BS EN 1340:2003 Inc. Corr. No. 1												
Breaking strength	Class 1 S - 3.5 MPa	Designation as section 5.3.3.1 & 2 BS EN 1340:2003 Inc. Corr. No. 1												
Slip/skid resistance	Satisfactory	Designation as section 5.3.5.1 BS EN 1340:2003 Inc. Corr. No. 1												
Thermal conductivity (Internal)	Not intended to contribute	Designation as section 5.3.7 BS EN 1340:2003 Inc. Corr. No. 1												
Durability	Satisfactory (linked to 5.3.3.1 & 2)	Designation as section 5.3.3.3 BS EN 1340:2003 Inc. Corr. No. 1												
Dangerous Substances	Regulatory information: Not classified as dangerous. The product contains no substances contained on either the Substances of Very High Concern (SVHC) in Annex XIV of European Regulation (EC) No. 06 (REACH); or the SVHC Candidate List	BS EN 771-3:2011+A1:2015. An informative database covering European and national provisions on dangerous substances is available via the following link: <a href="http://ec.europa.eu/enterprise/construction/cp-d-ds/">http://ec.europa.eu/enterprise/construction/cp-d-ds/</a>												
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site <a href="http://www.hoddamcontracting.co.uk">http://www.hoddamcontracting.co.uk</a> (or will be supplied directly). The appropriate DoP is referenced K4 UKCA DOP on the UKCA Regulations page and/or on the formal documentation	CPR DoP Electronic Provision No. 305/2011												


## 10. Declaration

The performance of the product identified in points 1 & 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for any on behalf of the manufacturer by Laura Gilfillan (General Manager), issued at the address given in point 4, 01 Jan 2023.

Signature: *Laura Gilfillan*

## Supporting information:

The UKCA Mark below was issued with your delivery ticket, or accompanying documentation in accordance with the CPR regulations. Accompanying documentation may include the quotation, order acknowledgement or invoice (delivered either in hard-copy or electronic format within an email).

	<b>BS EN 1340:2003 Inc. Corr. No.1</b> <u>UKCA Mark ref. K4 Dated 01 Jan 2023</u>			
<b>Concrete kerb units - Internal and External Flooring and/or roof covering</b>				
<b>Hoddam Contracting Company Limited</b>				
<b>Hoddam Road, Ecclefechan, Lockerbie, United Kingdom, DG11 3BY</b>				
<b>Product description: Concrete kerb units - Class 1 (see applicable variations below)</b>				
Intended use: Internal public transport premises, external uses and road finishes for pedestrian and vehicular areas, and roof coverings				
Attestation Level 4				
Essential Characteristics	Declared values (Applicable to Internal, External & Roof)		Test method	
Shape and dimensions (Type, profile and dimension)	<b>Class 1 Kerb Units</b> HB2R6EX HB2R8EX HB2R10EX	<b>Radius (external)/</b> 6m Half Batter HB2 8m Half Batter HB2 10m Half Batter HB2	<b>Dimensions (l*h*w) - mm</b> 780*255*125 780*255*125 780*255*125	Designation as Section 5.2 BS EN 1340:2003 Inc. Corr. No. 1 For client information only (Not an 'Essential Requirement' for CE Marking)
Reaction to fire (Internal)	Euroclass A1 w without test & Deemed to satisfy		Commission Decision 96/603/EC & 2000/553/EC (EN 1340:2003)	
Emission of asbestos	No content		Designation as section 4.2 BS EN 1340:2003 Inc. Corr. No. 1	
Breaking strength	Class 1 S - 3.5 MPa		Designation as section 5.3.3.1 & 2 BS EN 1340:2003 Inc. Corr. No. 1	
Slip/skid resistance	Satisfactory		Designation as section 5.3.5.1 BS EN 1340:2003 Inc. Corr. No. 1	
Thermal conductivity (Internal)	Not intended to contribute		Designation as section 5.3.7 BS EN 1340:2003 Inc. Corr. No. 1	
Durability	Satisfactory (linked to 5.3.3.1 & 2)		Designation as section 5.3.3.3 BS EN 1340:2003 Inc. Corr. No. 1	
Dangerous Substances	Regulatory information: Not classified as dangerous. The product contains no substances contained on either the Substances of Very High Concern (SVHC) in Annex XIV of European Regulation (EC) No. 06 (REACH); or the SVHC Candidate List		BS EN 771-3:2011+A1:2015. An informative database covering European and national provisions on dangerous substances is available via the following link: <a href="http://ec.europa.eu/enterprise/construction/cpd-ds/">http://ec.europa.eu/enterprise/construction/cpd-ds/</a>	
Declaration of Performance	In accordance with the CPR regulations, the Declaration of Performance (DoP) is held on our web site <a href="http://www.hoddamcontracting.co.uk">http://www.hoddamcontracting.co.uk</a> (or will be supplied directly). The appropriate DoP is referenced K4 UKCA DOP on the UKCA Regulations page and/or on the formal documentation		<b>CPR DoP Electronic Provision No. 305/2011</b>	

Please contact us should you require any further information.